



UL Style 1213

High Temperature Hook-Up Wire

TFE Teflon* Insulated .008" Min. Avg. Wall

Silver Plated Copper Conductor (Per ASTM B-298)

Voltage Rating: Not specified

Temperature: 105°C

Wire Type RDS Number	Gauge (AWG)	Dimensional Data		Weight LBS/1000' (Nominal)
		Stranding	Insulation O.D. Inches Nominal	
UL 1213				
E-32-01-**	32	1/32	.027	.69
E-32-07-**	32	7/40	.029	.78
E-30-01-**	30	1/30	.029	.88
E-30-07-**	30	7/38	.032	1.02
E-30-19-**	30	19/44	.032	1.03
E-28-01-**	28	1/28	.032	1.13
E-28-07-**	28	7/36	.035	1.32
E-28-19-**	28	19/40	.035	1.33
E-26-01-**	26	1/26	.035	1.51
E-26-07-**	26	7/34	.038	1.71
E-26-19-**	26	19/38	.038	1.74
E-24-01-**	24	1/24	.040	2.10
E-24-07-**	24	7/32	.043	2.41
E-24-19-**	24	19/36	.043	2.41
E-22-01-**	22	1/22	.046	2.99
E-22-07-**	22	7/30	.050	3.44
E-22-19-**	22	19/34	.050	3.47
E-20-01-**	20	1/20	.054	4.34
E-20-07-**	20	7/28	.058	5.05
E-20-19-**	20	19/32	.058	5.12
E-18-01-**	18	1/18	.061	6.50
E-18-07-**	18	7/26	.069	7.72
E-18-19-**	18	19/30	.069	7.80

** = Color.

0 = Black, 1 = Brown, 2 = Red, 3 = Orange, 4 = Yellow, 5 = Green, 6 = Blue, 7 = Violet, 8 = Grey, 9 = White
 These colors may also be used for stripe combinations. Example: -903 = White with one Black and one Orange stripe.