



UL Style 1007/1569

Dual Rated Wire

Appliance Wiring Material

Stranded Tinned Copper (Other coatings or Bare Copper also available)

PVC (Poly Vinyl Chloride Insulated) 1/64"

UL 1007 - 80°C 300 Volts

UL 1569 - 105°C 300 Volts

Wire Type RDS Number	Gauge (AWG)	Dimensional Data		Nominal Weight (lbs./1000')
		Stranding	Insulation O.D. (Nominal)	
UL 1007/1569	(AWG)	STANDARD STRANDING	(Nominal)	(lbs./1000')
1007-28-7 -**	28	7/36	.045	1.40
1007-26-7 -**	26	7/34	.048	1.80
1007-24-7 -**	24	7/32	.057	2.70
1007-22-7 -**	22	7/30	.065	3.80
1007-20-10-**	20	10/30	.072	4.90
1007-18-16-**	18	16/30	.080	7.20
1007-16-26-**	16	26/30	.094	10.80
1569-14-41-** ❖	14	41/30	.112	14.50

** = Color. See chart 1

❖ 14 AWG - UL 1569 Only

** = Color. See chart 1

Color Chart One	
0	Black
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Violet
8	Grey
9	White
Standard colors are listed above. Other colors may be available upon request. These colors may also be used for striped wire combinations	