



Appliance Wiring Material

Irradiated (Cross Linked) PVC (Poly Vinyl Chloride Insulated) .010"

UL 1429 - 80°C 150 Volts UL 1534 80°C Voltage Not Specified

MIL --W - 16878/1 105°C 600 Volts

Wire Type RDS Number	Gauge (AWG)	Dimensional Data		Nominal Weight (lbs./1000')
		Stranding	Insulation O.D. (Nominal)	
UL 1429	(AWG)	STANDARD STRANDING	(Nominal)	(lbs./1000')
1429-30-7 -**	30	7/38	.033	0.79
1429-28-7 -**	28	7/36	.036	1.09
1429-26-7 -**	26	7/34	.040	1.44
1429-26-19 -**	26	19/38	.040	1.58
1429-24-7 -**	24	7/32	.045	2.08
1429-24-19 -**	24	19/36	.045	2.14
1429-22-7 -**	22	7/30	.051	2.93
1429-22-19 -**	22	19/34	.052	3.17
1429-20-10-**	20	10/30	.058	4.21
1429-20-19 -**	20	19/32	.060	4.81
1429-18-19-**	18	19/30	.070	7.06
1429-16-19-**	16	19/29	.078	9.50
1534-14-19-❖❖	14	19/27	.096	13.82

\*\* = Color. See chart 1 ❖❖ : 14 AWG - UL 1534 Only

0	Black
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Violet
8	Grey
9	White

Standard colors are listed above. Other colors may be available upon request. These colors may also be used for striped wire combinations