



## DATASHEET UL Style 1571, 26 AWG

PVC Insulated Wire (Poly Vinyl Chloride)

0.004" nominal wall thickness

Max. Temperature 80°C Max. Voltage 30 Volts

Very Thin Wall, Small Diameter Wire, for use as internal wiring of Class 2 circuits in electronic equipment.

| RDS Item Number | Gauge | Stranding<br>(Tinned<br>Copper) | Insulation O.D.<br>(Nominal) | Nominal<br>Wall | DC<br>Resistance<br>@ 20°C<br>Ohms/1000ft |
|-----------------|-------|---------------------------------|------------------------------|-----------------|---|
| <b>UL 1571</b>  | (AWG) |                                 |                              |                 |   |
| 1571-26-07 -*   | 26    | 7/34                            | .027"                        | .004"           | 40.5                                      |

|               |        |
|---------------|--------|
| 1571-26-07 -0 | Black  |
| 1571-26-07 -1 | Brown  |
| 1571-26-07 -2 | Red    |
| 1571-26-07 -3 | Orange |
| 1571-26-07 -4 | Yellow |
| 1571-26-07 -5 | Green  |
| 1571-26-07 -6 | Blue   |
| 1571-26-07 -7 | Violet |
| 1571-26-07 -8 | Grey   |
| 1571-26-07 -9 | White  |

Black and White are standard stocking items.

Other colors on special order.

Also available with heavier insulation wall thickness on special order.