



MIL-I-3190 COATED FIBERGLASS SLEEVING

ASTM SIZE	INSIDE DIAMETER (INCHES)			Wall (Max)	Mil-I 3190 Size
	Nom	Min.	Max.		
24	.022	.020	.027	24	01
22	.027	.025	.032	22	02
20	.034	.032	.039	20	03
18	.042	.040	.049	18	04
17	.047	.045	.054	17	05
16	.053	.051	.061	16	06
15	.059	.057	.067	15	07
14	.066	.064	.074	14	08
13	.076	.072	.082	13	09
12	.085	.081	.091	12	10
11	.095	.091	.101	11	11
10	.106	.102	.112	10	12
9	.118	.114	.124	09	13
8	.133	.129	.141	08	14
7	.148	.144	.158	07	15
6	.166	.162	.178	06	16
5	.186	.182	.198	05	17
4	.208	.204	.224	04	18
3	.234	.229	.249	03	19
2	.263	.258	.278	02	20
1	.294	.289	.311	01	21
0	.330	.325	.347	00	22
3/8	.387	.375	.399	.375	23
7/16	.450	.438	.462	.438	24
1/2	.512	.500	.524	.500	25
5/8	.640	.625	.655	.625	26
3/4	.768	.750	.786	.750	27
7/8	.893	.875	.911	.875	28
1"	1.018	1.00	1.036	1.000	29

M3190/2 Vinyl Coated FiberGlassRDS Part Number: **3190/2 or BA1**

Class 130 (Temperature 130°C), Type B Category B

Dielectric Breakdown: 7000volts (NEMA)

M3190/3 Acrylic Coated FiberGlassRDS Part Number: **3190/3 or FA1**

Class 155 (Temperature 155°C) Type A Category A

Dielectric Breakdown: 7000volts (NEMA)

M3190/5 Silicone Resin Coated FiberGlassRDS Part Number: **3190/5 or HA1 Resin**

Class 200 (Temperature 200°C) Type C Category C

Dielectric Breakdown: 7000volts (NEMA)

M3190/6 Silicone Rubber Coated FiberGlassRDS Part Number: **3190/6 or HA1**

Class 200 (Temperature 200°C) Type D Category C

Dielectric Breakdown: 7000volts (NEMA)

M3190/7 Viton® Coated FiberGlassRDS Part Number: **3190/7 or RA1**

Class 220 (Temperature 220°C) Type E Category C

Dielectric Breakdown: 7000volts (NEMA)

Standard color: BLACK

M3190/8 Silicone Rubber Coated FiberGlassRDS Part Number: **3190/8**

Class 220 (Temperature 220°C) Type D Category C

Dielectric Breakdown: 7000volts (NEMA)

M3190/9 Silicone Rubber Coated FiberGlassRDS Part Number: **3190/9**

Class 240 (Temperature 240°C) Type D Category C

Dielectric Breakdown: 7000volts (NEMA)

Colors: Natural & White (standard), Black, Yellow, Red, Blue.
Other NEMA Grades are also available. Consult our sales staff.

Ordering information: Specify RDS Part Number, Size, and Color.