



Bare Copper Flat Braid

Bare Copper Flat Braid made in accordance with QQB575 and AA59569 for applicable sizes, however Bare Copper is not included in those specifications.

Braids are constructed from Copper with individual ends that conform to ASTM-B 3.

These Flat Braids are fabricated in round form and then mill rolled to meet a specific width and thickness.

Common use: Ground straps where flexibility is of concern.

RDS Part Number	Nominal Flat Width	AWG of ends	Construction	Aprox. AWG Equiv.	Weight Lbs/1000' (Nominal)	Current Capacity (AMPS)
QQBF-0-025-36BC	.025"	36	8 x 1 x 36	27	3	4.0
QQBF-0-062-36BC	3/32"	36	24 x 2 x 36	19	7	11.0
QQBF-0-109-36BC	5/32"	36	24 x 4 x 36	16	11	19.0
QQBF-0-125-36BC	1/8"	36	24 x 3 x 36	18	9	16.0
QQBF-0-156-36BC	1/4"	36	24 x 10 x 36	12	23	40.0
QQBF-0-187-36BC	3/16"	36	24 x 5 x 36	15	13	25.0
QQBF-0-250-36BC	1/4"	36	24 x 7 x 36	14	18	32.0
QQBF-0-375-30BC	3/8"	30	24 x 5 x 30	9	47	60.0
QQBF-0-375-36BC	3/8"	36	48 x 6 x 36	12	28	40.0
QQBF-0-500-30BC	1/2"	30	24 x 10 x 30	6	83	93.0
QQBF-0-500-36BC	1/2"	36	48 X 8 X 36	10	39	53.0
QQBF-0-625-30BC	5/8"	30	24 x 15 x 30	5	121	120.0
QQBF-0-625-36BC	5/8"	36	48 x 8 x 36	10	39	53.0
QQBF-0-750-30BC	3/4"	30	24 x 20 x 30	3	170	145.0
QQBF-0-750-36BC	3/4"	36	48 x 18 x 36	7	75	85.0
QQBF-0-875-30BC	7/8"	30	24 X 24 X 30	3	193	165.0
QQBF-1-000-30BC	1"	30	24 x 32 x 30	1	270	195.0
QQBF-1-000-36BC	1"	36	48 x 18 x 36	7	75	85.0
QQBF-1-375-30BC	1 3/8"	30	48 x 7 x 30	5	129	100.0