



UL Style 1371

High Temperature Hook-Up Wire

TFE Teflon® Insulated .0055" Minimum Average Wall Thickness

Silver Plated Copper Conductor (Per ASTM B-298)

Voltage Rating: Not Specified by UL

Temperature: +105°C

Use: Internal Wiring, where not subjected to movement or mechanical damage.

Wire Type RDS Number	Gauge (AWG)	Dimensional Data		Nominal Weight Lbs./1,000'
		Stranding	Insulation O.D.	
UL1371	(AWG)		Nominal Inches	
1371-36-01-*	36	1/36	.013-.019	.270
1371-36-07-*	36	7/44	.014-.020	.300
1371-34-01-*	34	1/34	.014-.020	.340
1371-34-07-*	34	7/42	.015-.021	.380
1371-32-01-*	32	1/32	.016-.022	.450
1371-32-07-*	32	7/40	.020-.024	.480
1371-32-19-*	32	19/44	.020-.024	.520
1371-30-01-*	30	1/30	.020-.024	.590
1371-30-07-*	30	7/38	.022-.026	.660
1371-30-19-*	30	19/42	.022-.026	.680
1371-28-01-*	28	1/28	.023-.027	.800
1371-28-07-*	28	7/36	.025-.029	.910
1371-28-19-*	28	19/40	.025-.029	.980
1371-26-01-*	26	1/26	.026-.030	1.16
1371-26-07-*	26	7/34	.029-.033	1.30
1371-26-19-*	26	19/38	.029-.033	1.40
1371-24-07-*	24	7/32	.034-.038	1.90
1371-24-19-*	24	19/36	.034-.038	2.02
1371-22-07-*	22	7/30	.040-.044	2.80
1371-22-19-*	22	19/34	.040-.044	3.98
1371-20-07-*	20	7/28	.048-.052	4.24
1371-20-19-*	20	19/32	.048-.052	4.60

* = Color.

0 = Black, 1 = Brown, 2 = Red, 3 = Orange, 4 = Yellow, 5 = Green, 6 = Blue, 7 = Violet 8 = Grey, 9 = White

These colors may also be used for stripe combinations. Example: -96 = White with one Blue stripe.